Notes:

- Pressure Rating: PN25
- Working Medium: Water, Oil, Steam
- Blow-out proof stem
- Full bore chrome plated ball
- PTFE seats and stem seals.
- BS21 Taper Threaded (ISO 7) / BS EN10226-2
- Available with NPT Threads, subject to minimum quantities

Dimensions

| DN | | | Н | D |
|--------|----|-------|------|-----|
| Inches | MM | L | П | D |
| 1/2" | 15 | 53 | 60 | 95 |
| 3/4" | 20 | 61 | 69 | 110 |
| 1" | 25 | 71 | 73 | 110 |
| 1¼" | 32 | 85 | 86.9 | 140 |
| 1½" | 40 | 92 | 91.4 | 140 |
| 2" | 50 | 114.5 | 106 | 161 |

All dimensions are nominal (indicative) Actual dimensions may vary

Material Specifications

| Description | Material | | |
|-------------------|------------------------------|--|--|
| Description | Material | | |
| Seat | PTFE | | |
| Ball | Brass CW617N (Chrome Plated) | | |
| Body | Bronze CC491K | | |
| Stem | DZR Brass CW602N | | |
| Extension Stem | Brass CW617N | | |
| Extension Housing | Brass CW617N | | |
| Lever | Mild Steel (Chrome Plated) | | |
| Lever Cover | PVC | | |





